



General Performance Data

Engine	Brand	SDEC
	Model	6DTAA8.9-G24
Control module		DEEP SEA 6120
Starting voltage	V	12V
Frequency	Hz	50
Number of phases		3


	Prime	Standby	
Power kVA	200	250	
Power kW	180	200	
Rated speed	r.p.m	1500	
Standard voltage	V	400	230
Available voltages	V	380/220	415/240
Power factor	Cos Phi	8	

Open



Dimension			
Length (L)	mm	2600	
Height (H)	mm	1835	
Width (W)	mm	1035	
Weight	Kg	2100	
Fuel Tank	L	450	

Silent



Dimension			
Length (L)	mm	3608	
Height (H)	mm	2007	
Width (W)	mm	1144	
Weight	Kg	2600	
Fuel Tank	L	450	

Fuel Consumption

Rated Output	g/KW.h	L/h
100% Standby	0000	49.6
100% Prime	0000	44.1
75% Prime	0000	32.8
50% Prime	0000	22.8
25% Prime	0000	0000

Standards Followed

ISO9001	ISO14001
ISO8528	ISO12100
ISO13849	EN12601
GB12786	GB/T2820
IEC60034	IEC60204
CE	RETIE

General Engine Data


Engine brand	SDEC	
Engine ref.	6DTAA8.9-G24	
Engine type	4-stroke diesel	
Governor type	Electronic	
Injection	Direct	
Aspiration	Turbo charged and Intercooled	
Number of cylinders and arrangement	6 - L	
Bore and stroke	mm	114x144

Displacement	L	8.82
Cooling system	Water	
Lube oil consumption with full load	0.5%-1% of fuel	
Compression ratio	18:1	
Engine oil capacity	L	30
Total coolant capacity	L	40
Air filter	Type	Dry

Diesel engine	Dry air filter
4-stroke cycle	Radiator with pusher fan
Water-cooled	Electronic governor
12V electrical system	Hot parts protection
Water separator filter	Moving parts protection

Optionals

Water jacked heater
Radiator water level sensor
Oil heater
Heavy duty air filter




Alternator Specifications

Brand	Stamford/AGG	
Number of phase	3	
Power factor	0.8	
Poles	4	
Winding Connections (standard)	Star- Series	
Insulation	H class	
Enclosure (according IEC-34-5)	IP23	

Model	KK274L	
Excitation system	Auxiliary coil brush-	
Voltage regulator	Electronic	
No. of bearings	Single Bearing	
Coupling system	Flexible disc	
Coating type	Standard (Vacuum impregnation)	

Optionals

Self-excited and self-regulated	Alternator pre-heater
IP23 protection	Winding temp. measuring instrument
H class insulation	PMG / AREP / MAUX



Application Data

Fuel system	Open	Silent
Fuel oil specifications	450	450
Standard fuel tank capacity	L	DIESEL

Air system		
Intake air flow	L/s	9.1 m3/min
Cooling air flow	m ³ /s	304.5 m3/min

Exhaust system		
Maximum exhaust temperature	°C	600
Exhaust gas flow	L/s	39.5m3/min
Maximum allowed back pressure	kPa	6

Starting system		
Starting power	kW	4
Recommended battery	Ah	2X120Ah
Number of batteries		2
Auxiliary voltage	Vdc	24V

Genset version

Steel chasis	High mechanical strength
Emergency stop button	Epoxy polyester powder coating
Anti-vibration shock absorbers	Fuel tank drain plug
Chassis with integrated fuel tank	Steel residential silencer - 20dbA attenuation
Fuel level gauge	Battery charger

Optionals

Trailer type

 Water-cooled

 Three phase

 50 Hz

 Diesel

 Dual-wall fuel tank

Optional

Standard reference conditions

Ambient conditions of reference according to ISO 8528-1:2018 normative: 1000 mbar, 25°C, 30% relative humidity.

Weights and dimensions based on standard products. Illustrations may include optional equipment. Technical data described in this catalogue correspond to the available information at the moment of printing.

Control Panel Data

Features of the control panel	Basic Model (Standard)	Advanced Model (Optional)
Voltage between phases	o	o
Voltage between neutral and phase	o	o
Current intensities	o	o
Frequency	o	o
Apparent power (kVA)	o	o
Active power (kW)	o	o
Reactive power (kVAr)	o	o
Power factor	o	o
Voltage between phases	o	o
Emergency stop	o	o
Binary inputs	6/6	7/7
Analog inputs	3	3
2x10A Current outputs	o	-
I/O Configuration	o/o	o/o
D+ Function	o/o	o/o
Speed sensor	o/o	o
Amf/Mrs	o	o
GCB/MCB	o	o
3ph voltage measurement Gen./Mains	o	o
3ph current measurement	o	o
kW / kWh / kVA	o	o
Engine reading	o	o
Engine protection	o	o
Alternator protection	o	o
Earth current protection	o	o
History file	150	350
RTC/Battery	o/-	o/o
PLC	-	-
4G	x	-
Airgate	-	x
ECU CAN	o	o
MODBUS	x	x
MODBUS IP	x	x
SNMP	-	x
SNMP TRAPS	-	-
RS232	x	x
RS485	x	x
GSM/GPRS modem	x	x
Remote screen	x	x
Software for PC	x	x

Standard: o Optional: x Not Available: -